

REWARDING BRIGHTNESS




## Downlights

## Curion 185 MLM Fixed

### Specifications

Colour white	Matte white RAL 9016 (XX=MW)
Colour black	Matte black RAL 9005 (XX=BL)
Beam angle (FWHM)	80°
Fixture material	Diecast aluminium
Environment	Indoor
IP rate	IP20 / IP44
IK rate	IK02
Operating temperature (Ta)	-20°C / +45°C
Safety marks	EN60598 / EN62031 / EN62471
EMC compliance	EN55015
Warranty	7 Years


 This luminaire contains  
built-in LED lamps

 The lamps cannot be changed in  
the luminaire.


874/2012



185 mm



185-205 mm



**185 mm:** For soft ceiling tiles. We recommend using a wooden plate or a ceiling ring on the reverse side of the tile.  
**185-205 mm:** For plasterboard ceilings or similar harder materials.

Only when the product is installed in a closed ceiling may it be exposed to water splashes, and only on its front side.

### Item specifications CRI80

(part A)

Description	Item code	Type	W	Lm/W	Input	CRI (typ.)	Pf	Inrush current	B-16A Fuse	Energy class
Curion 185 MLM 2400 Lm 3000K No dim	956703XX6602	Incl. PSU	22W	96 Lm/W	220-240V	83	0.95	5A 50uS	50 pcs	A+
Curion 185 MLM 2500 Lm 4000K No dim	956703XX6702	Incl. PSU	22W	100 Lm/W	220-240V	83	0.95	5A 50uS	50 pcs	A+
Curion 185 MLM 2400 Lm 3000K 1-10V	956703XX4302	Incl. PSU	22W	96 Lm/W	220-240V	83	0.95	5A 50uS	50 pcs	A+
Curion 185 MLM 2500 Lm 4000K 1-10V	956703XX4402	Incl. PSU	22W	100 Lm/W	220-240V	83	0.95	5A 50uS	50 pcs	A+
Curion 185 MLM 2400 Lm 3000K DALI	956703XX4602	Incl. PSU	22W	96 Lm/W	220-240V	83	0.92	5A 50uS	50 pcs	A+
Curion 185 MLM 2500 Lm 4000K DALI	956703XX4702	Incl. PSU	22W	100 Lm/W	220-240V	83	0.92	5A 50uS	50 pcs	A+
Curion 185 MLM 3500 Lm 3000K No dim	956803XX6602	Incl. PSU	34W	92 Lm/W	220-240V	83	0.95	5A 50uS	50 pcs	A+
Curion 185 MLM 3650 Lm 4000K No dim	956803XX6702	Incl. PSU	34W	96 Lm/W	220-240V	83	0.95	5A 50uS	50 pcs	A+
Curion 185 MLM 3500 Lm 3000K 1-10V	956803XX4302	Incl. PSU	34W	92 Lm/W	220-240V	83	0.95	5A 50uS	50 pcs	A+
Curion 185 MLM 3650 Lm 4000K 1-10V	956803XX4402	Incl. PSU	34W	96 Lm/W	220-240V	83	0.95	5A 50uS	50 pcs	A+
Curion 185 MLM 3650 Lm 3000K DALI	956803XX4602	Incl. PSU	34W	92 Lm/W	220-240V	83	0.95	5A 50uS	50 pcs	A+
Curion 185 MLM 3500 Lm 4000K DALI	956803XX4702	Incl. PSU	34W	96 Lm/W	220-240V	83	0.95	5A 50uS	50 pcs	A+
Curion 185 MLM 4350 Lm 3000K No dim	956903XX6602	Incl. PSU	46W	89 Lm/W	220-240V	83	0.98	10A 200uS	30 pcs	A+
Curion 185 MLM 4500 Lm 4000K No dim	956903XX6702	Incl. PSU	46W	92 Lm/W	220-240V	83	0.98	10A 200uS	30 pcs	A+
Curion 185 MLM 4350 Lm 3000K 1-10V	956903XX4302	Incl. PSU	46W	89 Lm/W	220-240V	83	0.98	10A 200uS	30 pcs	A+
Curion 185 MLM 4500 Lm 4000K 1-10V	956903XX4402	Incl. PSU	46W	92 Lm/W	220-240V	83	0.98	10A 200uS	30 pcs	A+
Curion 185 MLM 4350 Lm 3000K DALI	956903XX4602	Incl. PSU	46W	89 Lm/W	220-240V	83	0.98	10A 200uS	30 pcs	A+
Curion 185 MLM 4500 Lm 4000K DALI	956903XX4702	Incl. PSU	46W	92 Lm/W	220-240V	83	0.98	10A 200uS	30 pcs	A+

(part B)

Description	Safety class	Weight	Dimensions single carton	Quantity per carton	Expected lifespan (25°C)		
					L70B50	L80B50	L90B50
Curion 185 MLM 2400 Lm 3000K No dim	II	1401 gr	233x233x85 mm	20 pcs	80.000 hrs	70.000 hrs	60.000 hrs
Curion 185 MLM 2500 Lm 4000K No dim	II	1401 gr	233x233x85 mm	20 pcs	80.000 hrs	70.000 hrs	60.000 hrs
Curion 185 MLM 2400 Lm 3000K 1-10V	II	1404 gr	233x233x85 mm	20 pcs	80.000 hrs	70.000 hrs	60.000 hrs
Curion 185 MLM 2500 Lm 4000K 1-10V	II	1404 gr	233x233x85 mm	20 pcs	80.000 hrs	70.000 hrs	60.000 hrs
Curion 185 MLM 2400 Lm 3000K DALI	II	1407 gr	233x233x85 mm	20 pcs	80.000 hrs	70.000 hrs	60.000 hrs
Curion 185 MLM 2500 Lm 4000K DALI	II	1407 gr	233x233x85 mm	20 pcs	80.000 hrs	70.000 hrs	60.000 hrs
Curion 185 MLM 3500 Lm 3000K No dim	II	1401 gr	233x233x85 mm	20 pcs	80.000 hrs	70.000 hrs	60.000 hrs
Curion 185 MLM 3650 Lm 4000K No dim	II	1401 gr	233x233x85 mm	20 pcs	80.000 hrs	70.000 hrs	60.000 hrs
Curion 185 MLM 3500 Lm 3000K 1-10V	II	1510 gr	233x233x85 mm	20 pcs	80.000 hrs	70.000 hrs	60.000 hrs
Curion 185 MLM 3650 Lm 4000K 1-10V	II	1510 gr	233x233x85 mm	20 pcs	80.000 hrs	70.000 hrs	60.000 hrs
Curion 185 MLM 3650 Lm 3000K DALI	II	1569 gr	233x233x85 mm	20 pcs	80.000 hrs	70.000 hrs	60.000 hrs
Curion 185 MLM 3500 Lm 4000K DALI	II	1569 gr	233x233x85 mm	20 pcs	80.000 hrs	70.000 hrs	60.000 hrs
Curion 185 MLM 4350 Lm 3000K No dim	I	1569 gr	233x233x85 mm	20 pcs	80.000 hrs	70.000 hrs	60.000 hrs
Curion 185 MLM 4500 Lm 4000K No dim	I	1576 gr	233x233x85 mm	20 pcs	80.000 hrs	70.000 hrs	60.000 hrs
Curion 185 MLM 4350 Lm 3000K 1-10V	I	1576 gr	233x233x85 mm	20 pcs	80.000 hrs	70.000 hrs	60.000 hrs
Curion 185 MLM 4500 Lm 4000K 1-10V	I	1576 gr	233x233x85 mm	20 pcs	80.000 hrs	70.000 hrs	60.000 hrs
Curion 185 MLM 4350 Lm 3000K DALI	I	1576 gr	233x233x85 mm	20 pcs	80.000 hrs	70.000 hrs	60.000 hrs
Curion 185 MLM 4500 Lm 4000K DALI	I	1576 gr	233x233x85 mm	20 pcs	80.000 hrs	70.000 hrs	60.000 hrs

All values are measured at 230V (+/- 7%)

### Dimensions

