

REWARDING BRIGHTNESS



Available colours



Standard colour



Special colours




Trackspots

Odion XL 3F

Specifications

Colour(s)	Matt white RAL9016 (XX=MW) / Black RAL 9005 (XX=BL) / Grey RAL 9006 (XX=GR) Front ring standard in black and special colours on request (white, blue, gold and silver)
Beam angle (FWHM)	18° / 37° / 60°
UGR (4H8H 70/50/20)	<19 (18° + 37°)
Fixture material	Diecast aluminium / Polycarbonate
Environment	Indoor
IK rate	IK02
Operating temperature (Ta)	-20°C / +45°C
Safety marks	EN60598 / EN62031 / EN 62471
EMC compliance	EN55015
Warranty	7 Years


 This luminaire contains
built-in LED lamps

 The lamps cannot be changed in
the luminaire.


874/2012



IP20

Item specifications

Description	Item code	Type	Inrush current	B-16A Fuse	Energy class	Safety class	Weight	Dimensions single carton	Quantity per carton
Odion XL 5700 Lm 4000K CRI80	350403XXYY02	No dim	10A 200µS	30 pcs	A+	I	1586 gr	251x241x123 mm	12 pcs
Odion XL 5000 Lm 3000K CRI80	350403XXYY02	No dim	10A 200µS	30 pcs	A+	I	1586 gr	251x241x123 mm	12 pcs
Odion XL 3750 Lm 3000K CRI96	350403XXYY02	No dim	10A 200µS	30 pcs	A+	I	1586 gr	251x241x123 mm	12 pcs

Lumen settings

Odion 4000 K CRI 80

Item code	mA	W	Lm	Lm/W	PF	CRI (typ.)	Expected lifespan (25°C)			UGR		
							L70B50	L80B50	L90B50	18°	37°	60°
Special request	900	35,8	3850	108	0.93	82	131.000 hrs	80.000 hrs	35.000 hrs	15.8	16.8	21.3
Special request	1050	41,5	4400	106	0.94	82	129.000 hrs	78.000 hrs	33.000 hrs	16.3	17.3	21.7
Special request	1200	48,4	5000	103	0.94	82	129.000 hrs	78.000 hrs	33.000 hrs	16.7	17.8	22.2
350403XXYY02	1400	57,1	5700	100	0.95	82	129.000 hrs	78.000 hrs	33.000 hrs	17.2	18.2	22.6

XX= Matt white (MW) / Black (BL) / Grey (GR)

YY= 18° (HD), 37° (HE), 60° (HF)

Odion 3000 K CRI 80

Item code	mA	W	Lm	Lm/W	PF	CRI (typ.)	Expected lifespan (25°C)			UGR		
							L70B50	L80B50	L90B50	18°	37°	60°
Special request	900	35,8	3400	95	0.93	82	131.000 hrs	80.000 hrs	35.000 hrs	15.4	16.4	20.8
Special request	1050	41,5	3750	90	0.94	82	129.000 hrs	78.000 hrs	33.000 hrs	15.7	16.8	21.2
Special request	1200	48,4	4250	88	0.94	82	129.000 hrs	78.000 hrs	33.000 hrs	16.1	17.2	21.6
350403XXYY02	1400	57,1	5000	87	0.95	82	129.000 hrs	78.000 hrs	33.000 hrs	17.7	17.8	22.2

XX= Matt white (MW) / Black (BL) / Grey (GR)

YY= 18° (HA), 37° (HB), 60° (HC)


Odion 3000 K CRI 96

Item code	mA	W	Lm	Lm/W	PF	CRI (typ.)	Expected lifespan (25°C)			UGR		
							L70B50	L80B50	L90B50	18°	37°	60°
Special request	900	35,8	2700	75	0.93	96	131.000 hrs	80.000 hrs	35.000 hrs	14.6	15.6	20.0
Special request	1050	41,5	3000	72	0.94	96	129.000 hrs	78.000 hrs	33.000 hrs	14.9	16.0	20.4
Special request	1200	48,4	3250	67	0.94	96	129.000 hrs	78.000 hrs	33.000 hrs	15.2	16.3	20.7
350403XXYY02	1400	57,1	3750	66	0.95	96	129.000 hrs	78.000 hrs	33.000 hrs	15.7	16.8	21.2

XX= Matt white (MW) / Black (BL) / Grey (GR)

YY= 18° (HR), 37° (HS), 60° (HT)

Dimensions



Extra option

LEDs from the LUXEON Stylist Series
Specially developed for shops specialised in fashion or fresh food, and for restaurants. Ask our sales department about the possibilities.

