


REWARDING BRIGHTNESS




Trackspots

Odion XS 3F

Specifications

| | |
|----------------------------|---|
| Colour(s) | Matt white RAL9016 (XX=MW) / Black RAL 9005 (XX=BL) / Grey RAL 9006 (XX=GR) Front ring standard in black and special colours on request (white, blue, gold and silver) |
| Beam angle (FWHM) | 18° / 37° / 60° |
| UGR (4H8H 70/50/20) | <19 (18° + 37°) |
| Fixture material | Diecast aluminium / Polycarbonate |
| Environment | Indoor |
| IK rate | IK02 |
| Operating temperature (Ta) | -20°C / +45°C |
| Safety marks | EN60598 / EN62031 / EN 62471 |
| EMC compliance | EN55015 |
| Warranty | 7 Years |


IP20

Item specifications

| Description | Item code | Type | Inrush current | B-16A Fuse | Energy class | Safety class | Weight | Dimensions single carton | Quantity per carton |
|------------------------------|--------------|--------|----------------|------------|--------------|--------------|--------|--------------------------|---------------------|
| Odion XS 3400 Lm 4000K CRI80 | 350403XXYY02 | No dim | 5A 50µS | 50 | A+ | I | 840 gr | 251x241x123 mm | 12 pcs |
| Odion XS 3000 Lm 3000K CRI80 | 350403XXYY02 | No dim | 5A 50µS | 50 | A+ | I | 840 gr | 251x241x123 mm | 12 pcs |
| Odion XS 2400 Lm 3000K CRI96 | 350403XXYY02 | No dim | 5A 50µS | 50 | A+ | I | 840 gr | 251x241x123 mm | 12 pcs |

Lumen settings

Odion XS 4000 K CRI 80

| Item code | mA | W | Lm | Lm/W | PF | CRI (typ.) | Expected lifespan (25°C) | | | UGR | | |
|--------------|-----|------|------|------|------|------------|--------------------------|------------|------------|------|------|------|
| | | | | | | | L70B50 | L80B50 | L90B50 | 18° | 37° | 60° |
| On request | 700 | 27,6 | 3150 | 114 | 0.96 | 82 | 134.000 hrs | 82.000 hrs | 37.000 hrs | 15.1 | 16.2 | 20.6 |
| 350403XXYY02 | 800 | 32,1 | 3400 | 106 | 0.97 | 82 | 131.000 hrs | 80.000 hrs | 35.000 hrs | 15.4 | 16.4 | 20.8 |
| On request | 850 | 33,6 | 3500 | 104 | 0.97 | 82 | 131.000 hrs | 80.000 hrs | 35.000 hrs | 15.5 | 16.5 | 20.9 |

XX= Matt white (MW) / Black (BL) / Grey (GR)

YY= 18° (HN), 37° (HP), 60° (HQ)

Odion XS 3000 K CRI 80

| Item code | mA | W | Lm | Lm/W | PF | CRI (typ.) | Expected lifespan (25°C) | | | UGR | | |
|--------------|-----|------|------|------|------|------------|--------------------------|------------|------------|------|------|------|
| | | | | | | | L70B50 | L80B50 | L90B50 | 18° | 37° | 60° |
| On request | 700 | 27,6 | 2700 | 98 | 0.96 | 82 | 134.000 hrs | 82.000 hrs | 37.000 hrs | 14.6 | 15.6 | 20.0 |
| 350403XXYY02 | 800 | 32,1 | 3000 | 93 | 0.97 | 82 | 131.000 hrs | 80.000 hrs | 35.000 hrs | 14.9 | 16.0 | 20.4 |
| On request | 850 | 33,6 | 3100 | 92 | 0.97 | 82 | 131.000 hrs | 80.000 hrs | 35.000 hrs | 15.0 | 16.1 | 20.5 |

XX= Matt white (MW) / Black (BL) / Grey (GR)

Y= 18° (HK), 37° (HL), 60° (HM)


Odion XS 3000 K CRI 96

| Item code | mA | W | Lm | Lm/W | PF | CRI (typ.) | Expected lifespan (25°C) | | | UGR | | |
|--------------|-----|------|------|------|------|------------|--------------------------|------------|------------|------|------|------|
| | | | | | | | L70B50 | L80B50 | L90B50 | 18° | 37° | 60° |
| On request | 700 | 27,6 | 2200 | 94 | 0.96 | 96 | 134.000 hrs | 82.000 hrs | 37.000 hrs | 13.9 | 14.9 | 19.3 |
| 350403XXYY02 | 800 | 32,1 | 2500 | 78 | 0.97 | 96 | 131.000 hrs | 80.000 hrs | 35.000 hrs | 14.2 | 15.2 | 19.6 |
| On request | 850 | 33,6 | 2600 | 72 | 0.97 | 96 | 131.000 hrs | 80.000 hrs | 35.000 hrs | 14.3 | 15.3 | 19.8 |

XX= Matt white (MW) / Black (BL) / Grey (GR)

Y= 18° (HG), 37° (HH), 60° (HJ)

Dimensions



Extra option

LEDs from the LUXEON Stylist Series
Specially developed for shops specialised in fashion or fresh food, and for restaurants. Ask our sales department about the possibilities.

