

REWARDING BRIGHTNESS




Downlights

Fabio 75 MLMC Fixed

Specifications

| | |
|----------------------------|------------------------------|
| Colour white | Matte white RAL 9016 (XX=MW) |
| Colour grey | Matte grey RAL 9006 (XX=GR) |
| Colour black | Matte black RAL 9005 (XX=BL) |
| Beam angle (FWHM) | 60° |
| Fixture material | Diecast aluminium |
| Environment | Indoor, cove lighting |
| IP rate | IP20 / IP44 |
| IK rate | IK02 |
| Operating temperature (Ta) | -20°C / +45°C |
| Safety marks | EN60598 / EN62031 / EN62471 |
| EMC compliance | EN55015 |
| Warranty | 7 Years |


 This luminaire contains
built-in LED lamps

 The lamps cannot be changed in
the luminaire.


874/2012



75 mm

IP20
IP44

Only when the product
is installed in a closed
ceiling may it be
exposed to water
splashes, and only on
its front side.

REWARDING BRIGHTNESS

Item specifications

(part A)

| Description | Item code | Type | W | Efficacy | Input | CRI (typ.) | Pf | Inrush current | Energy class |
|----------------------------------|--------------|-----------|-----|----------|------------------|------------|----|----------------|--------------|
| Fabio 75 MLMC max. 1000 Lm 2700K | 837803XX42E2 | Excl. PSU | 17W | 59 Lm/W | Max. 700mA / 26V | 93 | X | X | A |
| Fabio 75 MLMC max. 1250 Lm 3000K | 837803XX43E2 | Excl. PSU | 17W | 74 Lm/W | Max. 700mA / 26V | 83 | X | X | A |
| Fabio 75 MLMC max. 1500 Lm 4000K | 837803XX44E2 | Excl. PSU | 17W | 88 Lm/W | Max. 700mA / 26V | 83 | X | X | A |

(part B)

| Description | Safety class | Weight | Dimensions single carton | Quantity per carton | Expected lifespan (25°C) | | |
|----------------------------------|--------------|--------|--------------------------|---------------------|--------------------------|------------|------------|
| | | | | | L70B50 | L80B50 | L90B50 |
| Fabio 75 MLMC max. 1000 Lm 2700K | III | 327 gr | 105x105x61 mm | 42 pcs | 162.137 hrs | 99.652 hrs | 44.082 hrs |
| Fabio 75 MLMC max. 1250 Lm 3000K | III | 327 gr | 105x105x61 mm | 42 pcs | 162.137 hrs | 99.652 hrs | 44.082 hrs |
| Fabio 75 MLMC max. 1500 Lm 4000K | III | 327 gr | 105x105x61 mm | 42 pcs | 162.137 hrs | 99.652 hrs | 44.082 hrs |

All values are measured at 230V (+/- 7%)

Choose your power supply - 26V

| Lamp current | Lamp Wattage | Lumen Output | | | Lumen / Watt | | | DALI Ripple < 3% | 1-10V Ripple < 3% | NO DIM Ripple < 3% | NO DIM Ripple < 20% | TRIAC Ripple < 20% |
|--------------|--------------|--------------|-------|-------|--------------|-------|-------|-------------------|-------------------|--------------------|---------------------|--------------------|
| | | 2700K | 3000K | 4000K | 2700K | 3000K | 4000K | | | | | |
| 350 mA | 8,5W | 525 | 675 | 800 | 62 | 79 | 94 | 05CD ² | 05CC ² | 05BZ ² | 05CV ² | x |
| 500 mA | 12W | 715 | 900 | 1075 | 60 | 75 | 90 | 05CD ² | 05CC ² | 05BZ ² | 05CV ² | x |
| 700 mA | 17W | 1000 | 1250 | 1500 | 59 | 74 | 88 | 05CD ¹ | 05CC ¹ | 05BZ ¹ | 05CV ¹ | 05CB ¹ |

¹ Standard setting. ² Can be set during installation by adjusting DIP-switch settings.

Dimensions

